



网站: www.lieyankeji.com
 邮箱: cn1837416888@gmail.com
 备注: 本产品随技术进步不断更新改进, 如有修改, 恕不另行通知。以上内容最终解释权归本公司所有。

公司简介

湖南烈岩科技有限公司, 主要从事液压破碎锤的研发、生产和销售。公司积累了丰富的生产破碎锤的经验, 工程建设中特别是对混凝土拆除和矿山作业优势更为明显。公司始终把产品质量视为企业的生命, 秉承“真挚, 求实, 发展”的企业理念, 以不断为客户创造价值为追求目标, 立志打造工程机械市场知名品牌, 以过硬的质量和售后服务拓展市场, 以品牌求发展, 实现与客户的互利共赢。



BRIEF INTRODUCTION



Hunan Lieyan Technology Co., Ltd. is primarily engaged in the research and development, production, and sales of hydraulic breakers. The company has accumulated extensive experience in manufacturing breakers, with its products exhibiting particular advantages in engineering construction, especially in concrete demolition and mining operations. The company has always regarded product quality as its life-blood, adhering to the corporate philosophy of "Sincerity, Pragmatism, and Development". It pursues the goal of continuously creating value for customers, strives to build a renowned brand in the construction machinery market, expands its market with excellent quality and service, and pursues development through branding to achieve mutual benefit and win-win results with its customers.



公司文化 CULTURE

诚信精神: 持之以恒, 精益求精, 不断超越
诚信愿景: 成为领先的挖掘机械附件制造商
诚信目标: 成为一流的液压破碎锤制造商
经营理念: 诚信为本, 创新为魂
质量方针: 一丝不苟、精益求精, 为顾客提供优质的产品
 和满意的服务, 使企业的质量管理体系得到持续改进。
服务理念: 客户至上, 用心服务

CHLB Spirit: Perseverance, excellence, and constantly transcend
CHLB Vision: To be the world's leading excavator attachment manufacturer
CHLB Goal: To be the world class hydraulic breaker manufacturer
Business Philosophy: Honesty, innovation as the soul
Quality Policy: Meticulous, excellence, to provide customers with quality products and satisfactory service, make the enterprise quality management system continuously improved.
Service Concept: Customer first, intentions services



三角型破碎锤 SIDE TYPE HYDRAULIC BREAKER

产品特点
 容易控制, 定位方便
 持久耐用, 工作效率高
 打击力强, 使用寿命超长
 操作性能稳定, 售后服务便捷

CHARACTERISTIC
 Easy to control and convenient to position
 Durable and durable, and high working efficiency
 High impact force and long service life
 The operation performance is stable and after-sales service is convenient



型号 Model	Unit	小型液压破碎锤范围 Small Range						中型液压破碎锤范围 Medium Range						
		LYP5180	LYP5200	LYP5300	LYP5350	LYP5400	LYP5430	LYP5450	LYP5800	LYP51600	LYP52000	LYP52200	LYP52200A	LYP53000
适配挖掘机 Suitable Excavator	ton	0.8-2.5	1.2-3.0	2.5-4.5	3.0-5.5	4-7	6-9	7-14	10-15	15-18	18-26	18-26	18-26	25-30
总重量 Operating Weight	kg	77	99	132	198	275	418	561	842	1381	1809	1950	1950	2359
流量 Required Oil Flow	l/min	15-30	20-40	25-50	30-40	40-70	50-90	60-100	80-110	90-120	100-150	120-180	120-180	150-210
设定压力 Setting Pressure	bar	150	150	150	150	170	180	190	200	210	210-230	210-230	210-230	240-250
液压压力 Operating pressure	bar	90-120	90-120	90-120	100-130	110-140	120-150	130-160	150-170	150-170	160-180	160-180	160-180	180-180
冲击力 Impact Energy	psule	203	271	406	542	877	1017	1355	2033	2711	3423	4067	4067	5423
打击频率 Impact Rate	bpm	800-1400	700-1200	600-1100	500-1000	300-450	400-800	400-800	350-700	350-650	350-600	350-500	350-500	300-450
软管直径 Hose Diameter	inch	1/2	1/2	1/2	1/2	1/2	1/2	3/4	3/4	1	1	1	1	1
声音分贝数 Noise level	dB	106	107	109	117	109	115	112	114	115	120	118	118	120
钎杆直径 Tool Diameter	mm	40	45	53	60	68	75	85	100	125	135	140	140	150



型号 Model	Unit	大型范围 Large Range						大型范围 Large Range						
		LYP5200	LYP5300	LYP5300F	LYP5400	LYP5800G	LYP54000G	LYP5185	LYP5195	LYP5195P	LYP5200	LYP5205	LYP5210	LYP5220
适配挖掘机 Suitable Excavator	ton	28-35	30-40	30-40	35-40	25-33	35-45	35-45	40-55	50-55	50-70	50-70	60-80	70-80
总重量 Operating Weight	kg	2655	2735	3289	4167	2462	3001	4378	5039	5374	6205	6375	6683	7378
流量 Required Oil Flow	l/min	180-240	200-260	200-260	210-290	175-220	200-250	220-290	240-290	260-280	260-300	300-350	300-350	300-450
设定压力 Setting Pressure	bar	240-260	240-260	240-260	260-280	210	210	290-300	300-310	300-310	300-310	310-330	310-330	350
液压压力 Operating pressure	bar	180-200	180-200	180-200	180-200	160-180	160-180	220-280	220-280	260-280	220-280	260-280	260-320	280-320
冲击力 Impact Energy	psule	6779	8812	10846	12202	5193	10388	14302	17088	19322	21360	23543	25632	27057
打击频率 Impact Rate	bpm	300-450	250-400	250-350	250-350	300-450	300-400	200-250	180-200	160-200	150-200	150-200	150-200	120-180
软管直径 Hose Diameter	inch	1-1/4	1-1/4	1-1/4	1-1/4	1	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4
声音分贝数 Noise level	dB	123	123	124	125	120	123	125	125	125	125	125	125	125
钎杆直径 Tool Diameter	mm	155	165	165	175	150	160	185	195	195	200	205	210	220

直角型破碎锤 TOP TYPE HYDRAULIC BREAKER

产品特点
 强大的打击力;
 卓越的环保性能;
 精湛的制造工艺;
 保养简单, 售后服务快捷。

PRODUCT FEATURES
 Strong impact power;
 Excellent environmental performance;
 Excellent manufacturing technology;
 Easy maintenance, fast after-sales service.



型号 Model	Unit	小型液压破碎锤范围 Small Range						中型液压破碎锤范围 Medium Range						
		LYP5180	LYP5200	LYP5300	LYP5350	LYP5400	LYP5430	LYP5450	LYP5800	LYP51600	LYP52000	LYP52200	LYP52200A	LYP53000
适配挖掘机 Suitable Excavator	ton	0.8-2.5	1.2-3.0	2.5-4.5	3.0-5.5	4-7	6-9	7-14	10-15	15-18	18-26	18-26	18-26	25-30
总重量 Operating Weight	kg	77	121	148	224	321	419	638	979	1463	1698	2050	2050	2271
流量 Required Oil Flow	l/min	15-30	20-40	25-50	30-40	40-70	50-90	60-100	80-110	90-120	100-150	120-180	120-180	150-210
设定压力 Setting Pressure	bar	150	150	150	150	170	180	190	200	210	210-230	210-230	210-230	240-250
液压压力 Operating pressure	bar	90-120	90-120	90-120	100-130	110-140	120-150	130-160	150-170	150-170	160-180	160-180	160-180	180-180
冲击力 Impact Energy	psule	203	271	406	542	877	1017	1355	2033	2711	3423	4067	4067	5423
打击频率 Impact Rate	bpm	800-1400	700-1200	600-1100	500-1000	300-450	400-800	400-800	350-700	350-650	350-600	350-500	350-500	300-450
软管直径 Hose Diameter	inch	1/2	1/2	1/2	1/2	1/2	1/2	3/4	3/4	1	1	1	1	1
声音分贝数 Noise level	dB	106	107	109	117	109	115	112	114	115	120	118	118	120
钎杆直径 Tool Diameter	mm	40	45	53	60	68	75	85	100	125	135	140	140	150



型号 Model	Unit	大型范围 Large Range						大型范围 Large Range						
		LYP5200	LYP5300	LYP5300F	LYP5400	LYP5800G	LYP54000G	LYP5185	LYP5195	LYP5195P	LYP5200	LYP5205	LYP5210	LYP5220
适配挖掘机 Suitable Excavator	ton	28-35	30-40	30-40	35-40	25-33	35-45	35-45	40-55	50-55	50-70	50-70	60-80	70-80
总重量 Operating Weight	kg	3059	3151	3503	4216	2591	3158	4809	5164	5504	6408	6505	6993	7508
流量 Required Oil Flow	l/min	180-240	200-260	200-260	210-290	175-220	200-250	220-290	240-290	260-280	260-300	300-350	300-350	300-450
设定压力 Setting Pressure	bar	240-260	240-260	240-260	260-280	210	210	290-300	300-310	300-310	300-310	310-330	310-330	350
液压压力 Operating pressure	bar	180-200	180-200	180-200	180-200	160-180	160-180	220-280	220-280	260-280	220-280	260-280	260-320	280-320
冲击力 Impact Energy	psule	6779	8812	10846	12202	5193	10388	14302	17088	19322	21360	23543	25632	27057
打击频率 Impact Rate	bpm	300-450	250-400	250-350	250-350	300-450	300-400	200-250	180-200	160-200	150-200	150-200	150-200	120-180
软管直径 Hose Diameter	inch	1-1/4	1-1/4	1-1/4	1-1/4	1	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4
声音分贝数 Noise level	dB	123	123	124	125	120	123	125	125	125	125	125	125	125
钎杆直径 Tool Diameter	mm	155	165	165	175	150	160	185	195	195	200	205	210	220